

Engine Specification Sheet



Model	Ratings HP (kW) @ Rated speed rpm	
	1470	1760
CH6-159-EB (UL)	680(507)	783(584)
CH6-159-EB (FM)		778 (580)

ENGINE SPECIFICATIONS		
Basic Engine	Chongqing Cummins	
Type	4 Cycle; In-line; water cooled; 6 Cylinder	
Aspiration	Turbocharged +Water Cooled	
Bore and Stroke	mm×mm	159x159
Displacement	L	18.9
Compression Ratio	13.9:1	
Rotation Viewed from flywheel	Counter Clockwise	
Dry Weight Approx.	kg	2475
Dimension Approx. (L*W*H)	mm	2250*1380*1935
Crankshaft Centerline Height	mm	440
Oil Capacity	L	38
Coolant Capacity - Engine + Heat Exchanger	L	80



MODEL
CH6-159-EB

Engine Equipment	Standard	Optional	
Air Cleaner	Drip proof	N/A	
Alternator	24V-DC, 35Amps with Belt Guard	N/A	
Coupling	Bare Flywheel	N/A	
Engine Heater	220V-AC	110V-AC	
Exhaust Flex Connection	DN125	N/A	
Exhaust Protection	Metal Guard	N/A	
Flywheel Housing	SAE 0	N/A	
Flywheel Power Take Off	SAE 14	N/A	
Fuel Connections	Flexible hoses according ISO 15540	N/A	
Fuel Filter	Full flow, cartridge type	N/A	
Governor, Speed	Constant speed, mechanical	N/A	
Heat Exchanger	Shell and Tube Type	N/A	
Instrument Panel	Build on Engine	N/A	
Junction Box	Integrated in control panel	N/A	
Lube Oil Cooler	Jacket Water Cooled	N/A	
Lube Oil Filter	Full flow, cartridge type	N/A	
Lube Oil Pump	Gear Driven, Gear Type	N/A	
Manual Start Control	Dual Manual Start Contactors	N/A	
Overspeed Control	Electronic instrument panel, test on instrument panel	N/A	
Raw Water Cooling Loop w/ Alarms	Galvanized	Seawater (All 316 SS)	
Raw Water Solenoid Operation	Automatic from Fire Pump Controller and from Engine Instrument Panel (for Horizontal Fire Pump Applications)	N/A	
Run - Stop Control	On Instrument Panel with Control Position Warning Light	N/A	
Starters	24V-DC,9.5KW	N/A	
Throttle Control	Adjustable speed control	N/A	
Water Pump	Centrifugal Type, Gear Driven	N/A	
All data is based on the engine operating with fuel system, lubricating oil pump, air cleaner, and alternator; not included are compressor, fan, optional equipment, and driven components.;Data is based on operation at SAE standard J1394 conditions of 300ft (91,4m) altitude, 29.61 in.(752mm) Hg dry barometer, and 77°F (25°C) intake air temperature, using 0# diesel fuel follow the standard GB 252-2011.			
Altitude above which output should be Limited		m (ft.)	91 (300)
Correction Factor per 305m.(1,000ft.) above Altitude Limit		3%	
Temperature above which output should be Limited		°C (°F)	25 (77)
Correction Factor per 5.6°C (10°F) above Temperature Limit		1%	
Remark:			
1.All data certified within 5%;			
2.TBD - To Be Determined;			
3.N/A - Not Applicable;			



Engine Data Sheet

Engine Model	CH6-159-EB	Date	2020/12/23	
Drawing No.	CH6-159-EB.00	Performance Curve No.	C06159B	
Rated Power	783 HP @1760 RPM	Reference No.	14DS001E	
	584 KW @ 1760 RPM	Version	A	
GENERAL ENGINE DATA				
Type		4 Cycle;In-line; water cooled; 6 Cylinder		
Aspiration		Turbocharged +Water Cooled		
Bore and Stroke		mm×mm	159x159	
Cylinder Liner Type		<input checked="" type="checkbox"/> Wet	<input type="checkbox"/> Dry	
Displacement		L	18.9	
Compression Ratio		13.9:1		
Firing Order		1-5-3-6-2-4		
Combustion System		Direct Injection		
Rotation Viewed from front of engine		CW		
Valves Per Cylinder		Intake :2 Exhaust :2		
Valves lashes at cold	Intake	mm (inch)	0.36	
	Exhaust	mm (inch)	0.69	
Ignition Type		Compression(Diesel)		
Charge Air Cooling Type		Raw Water		
Dry Weight Approx.		kg	2475	
Dimension Approx. (L*W*H)		mm	2250*1380*1935	
Flywheel/ Flywheel House Dimension		14"/ SAE 0		
Torque at rated RPM		N.m	3170	
EXHAUST SYSTEM				
Exhaust Gas Temp. at max. rating/power		°C	502	
Exhaust Gas Flow at Max. output		m³/h	9265	
Max. Allowable Back Pressure		kpa	10	
Minimum Exhaust Pipe Diameter		DN	200	
AIR INTAKE SYSTEM				
Air Cleaner Type		Dry Type		
Air Flow at Max. output		m³/h	3485	
Air Inlet Restriction Dirty		kpa	6.2	
Air Inlet Restriction Clean		kpa	3.7	
LUBRICATION SYSTEM				
Oil Capacity		L	38	
Max. Sump Oil Temp.		°C	121	
Normal Operating Oil Pressure Range		bars	3.4~4.8	
Oil Pressure at Idle		bar	1.38	
COOLING SYSTEM				
Coolant Capacity - Engine + Heat Exchanger		L	80	
Thermostat Range	Start Open	°C	82	
	Full Open	°C	93	
Coolant Pressure Cap		bar	0.9	
Max. Engine Coolant Temp.		°C	96	
Engine Coolant Flow at Full Load		m³/h	45	
Raw Water Cooling Capacity		m³/h	25	




Engine Data Sheet

Raw Water Pressure		bar	2
Min. Raw Water Temp.		°C	15.6
	Raw Water Pipe Size	Raw Water Inlet	G2"
		Raw Water Outlet	G2 1/2"
HEATER SYSTEM			
Wattage		W	4500
Voltage AC		V	220
ELECTRICAL SYSTEM-DC			
System Voltage(Nominal)		V	24
Starter motor		Kw	9.5
Recommended Battery Capacity		AH	200
Cold Cranking Amperes @ -18°C (0°F)		CCA	1000
Reserve Capacity (RC)		Min	407
Charging Alternator Output		Amps	35
Max. Starter Cranking Amps @4.5°C (0°F)		Amps	665
Min. Cranking Speed Required for Unaided Cold Start		rpm	150
FUEL SYSTEM			
Injection Pump			
Injection Advance Angle		°	IQ
Minimum Supply line Size		mm	19
Minimum Return line Size		mm	16
Fuel Management Control		Mechanical	
Max. Fuel Consumption		g/kw,h	215
Idle Speed		rpm	675
Max. Governed Speed		rpm	1936
Maximum allowable fuel height above fuel pump		m	3
Governed Speed Rate		%	<10
Engine Performance Data			
Estimated free field soud pressure level at 1 meter with full-load governed speed(Includes Noise from: exhaust;: Cooling System and Driven Components)		dBa	108
All data is based on the engine operating with fuel system, lubricating oil pump, air cleaner, and alternator; not included are compressor, fan, optional equipment, and driven components.;Data is based on operation at SAE standard J1394 conditions of 300ft (91.4m) altitude, 29.61 in.(752mm) Hg dry barometer, and 77°F (25°C) intake air temperature, using 0# diesel fuel follow the standard GB 252-2011.			
Altitude above which output should be Limited		m (ft.)	91 (300)
Correction Factor per 305m.(1,000ft.) above Altitude Limit		3%	
Temperature above which output should be Limited		°C (°F)	25 (77)
Correction Factor per 5.6°C (10°F) above Temperature Limit		1%	
Remark:			
1.All daa certified within 5%;			
2.TBD - To Be Determined;			
3.N/A - Not Applicable;			



DIESEL ENGINE

Engine Model		CH6-159-EB		Curve No.		C06159B	Date	2021/1/6
Displacement	18.90	L	Aspiration	Turbocharged+Water cooled		Power Standard		UL/FM
Bore	159	mm	Cylinder Qty.	6, In Line		584	KW @ 1760	r/min
Stroke	159	mm	Fuel System	Mechanical		783	HP @ 1760	r/min



Torque		
Speed RPM	Torque	
	N-m	lb-ft.
1200		
1300		
1400		
1470	3296	2430
1760	3170	2338
2100		

Output Power		
Speed RPM	Output Power	
	KW	HP
1200		
1300		
1400		
1470	507	680
1760	584	783
2100		

Fuel Consumption		
Speed RPM	Consumption	
	g/KW-HR	lb/BHP-HR
1200		
1300		
1400		
1470	220	0.362
1760	213	0.350
2100		